


VISION TESTER

*VT-10*





# Versatility & Convenience combined with Unparalleled Response & Precision

Precision and convenience are a tradition in high quality TOPCON optical instruments.

The new VT-10 vision tester advances this tradition still further, making refraction quicker and easier than ever before, providing unequaled performance and exceptional versatility.


Precision in design and workmanship guarantees accuracy in refraction measurements—accuracy that won't deteriorate even after long years of use.

Total quality from TOPCON means you can have total confidence in the performance you'll enjoy from the VT-10 vision tester.






# Controls & Scales Make Refraction Comfortable Functional



## Wide Testing Range

The testing range available with the VT-10 is extraordinary, the standard cylinder power range extends to 6.00D in 0.25D increments. In addition, auxiliary lens sets are incorporated to fine-tune cylinder power measurements to 0.12D increments or extend cylinder power range to 8.00D. Accurate prism reading even below 0.5 $\Delta$  are possible thanks to the 20 $\Delta$  range (1 $\Delta$  increments) of the precision-gear rotary prism loupes. The VT-10 is also available in plus or minus cylinder models.




## Synchronized Cross-Cylinders

The most significant time-saving feature of the VT-10 is its synchronization of cross-cylinder loupe rotation to cylinder axis adjustment. Special gearing automatically synchronizes the rotation of the loupe each time you change cylinder axis correction. The result? You simply read a single scale, one time, after completing a full series of axis checks. The bi-loupe turret lets you index power or axis loupes with a single touch.



## Easy Controls & Clear Scales


Control of cylinder axis and power testing is amazingly simple; concentric control knobs within a double-calibration axis scale make adjustment a quick, one hand action through the full 360 $^\circ$  range. The axis scale reads in 5 $^\circ$  increments, with 15 $^\circ$  markings. An additional axis scale is located at the main aperture, for convenient reference during retinoscopy. The low position of the control knobs keeps the operator's hands out of the line of vision.




## Simple Convergence System




Precise measurements at both near and distant testing for optimal results.



One quick adjustment of the dual convergence levers and the VT-10 provide total accuracy in near vision testing measurement.



## Sealed Optics




The examination apertures feature cover lenses for convenience and protection. Dust, eyelashes, etc. can't get in, and the lenses are easily removed for simple cleaning. The patient always has a bright, clear image to view. (Standard accessories include face shields that can be sterilized for optimum comfort and hygiene.)



# es Designed to ion Quick & Features for Versatility


## Versatile Adjustments

Convenient dual controls make it easy for the operator to adjust interpupillary distance, in a range from 48mm to 75mm. The mechanism is sealed for protection and smooth functioning. An easy-to-read scale provides 1mm graduations, and a vergence adjustment controls reductions in P.D. during near testing.





## A Wide Range of Versatile Auxiliary Lenses

The TOPCON VT-10 comes with a full complement of versatile auxiliary lenses—10 different lenses plus two open apertures, any of which can be indexed into position with one-touch speed and convenience. A red lens/green lens shift, for example, is immediately available for binocular vision testing. The auxiliary lens plate has a flat black finish to prevent stray reflections during use.



## Fast, Precise Results

TOPCON VT-10 incorporates a single-dial power control that lets the operator quickly dial in any spherical power from +16.75D through 0 to -19.00D, in 0.25D increments. To make settings faster, a strong sphere control allows adjustment in 3.00D steps; the auxiliary lens knob provides for fine-tuning in 0.12D increments for absolute accuracy.



## ACCESSORIES

The holder for rotary near point card mounts to a sturdy rod with a distance scale from 5 to 28 inches—centimeter and diopter scales are included. A hinged bracket moves it into position immediately, or raises it out of the way. Accessory lenses come in an accessory box, holding dual sets or -0.12D and -2.00D cylinder lenses.

## OPTIONAL ACCESSORIES



$\pm 0.37/\pm 0.50D$  cross cylinder,  
+2.00D retinoscopic lens.

e  
h  
n  
  
igh  
adi-  
and  
per-  
ees  
acy  
of  
ve  
joy



# A Half-Century of Dedication to Superior Optical Instrumentation


TOPCON has remained a leader and major innovator in optical instrumentation and technology for more than half a century. Intensive dedication to engineering research and manufacturing precision has made TOPCON the name to know for reliable performance.

## Precision Engineering for Superior Performance;

Designed for total precision, the new VT-10 vision tester represents TOPCON optical engineering at its very best—extreme accuracy over the widest possible testing range. Internal mechanisms are precisely machined to the finest tolerances; parts and components are made from the finest materials, all corrosion-resistant and tested for performance and durability.

## Multi-Coated Lenses for Superior Optical Performance

Every lens used in the VT-10 receives a special multi-coating that eliminates flare, ghost images and reflections. In addition, the multi-coating assures clearer, brighter images with improved contrast and excellent color fidelity.



The TOPCON VT-10 is available in either black or gray finishes.



## SPECIFICATIONS

### Type

Subjective refraction testing equipment

### Item and range of measurement

The value in ( ) is with accessory lens or auxiliary lens attached:

Myopia	0 to -19.00D in 0.25D step (0.12D step)
Hyperopia	0 to +16.75D in 0.25D step (0.12D step)
Astigmatism	0 to -6.00D (-8.00D) in 0.25D step (0.12D step)
Cross-Cylinder	±0.25D (±0.37D and ±0.50D as option)
Phoria and vergency	20 <sup>Δ</sup> to 0 to 20 <sup>Δ</sup> by 1 <sup>Δ</sup> step Inner 40 <sup>Δ</sup> Outer 40 <sup>Δ</sup> (50 <sup>Δ</sup> ) Upward and Downward 40 <sup>Δ</sup> (46 <sup>Δ</sup> )
Near vision test	Main optical axes of both lenses converges by means of a tilt mechanism at 40cm in front of the eyes at 64mm P.D. If P.D. for far vision is less than 54mm, converging operation stops.
Binocular balance test	Rotary prism and polarizing lens methods are available.
P.D.	48 to 75mm by 1mm step
Level adjustment	More than 4.5° for right and left banks
Dimensions	335 (at 64mm P.D. setting) × 97 × 294mm
Weight	4.5kg

### Content of auxiliary lens dial:

"Q/O"—Open Aperture

"R"—Retinoscopic Lens: +1.50D standard  
+2.00D option

"P"—Polarizing Filter

"WMV/RMV"—Maddox Rod, vertical: white (left)  
red (right)

"WMH/RMH"—Maddox Rod, horizontal: white (left)  
red (right)

"GL"—Green Lens (left)

"RL"—Red Lens (right)

" +.12"—+0.12D Spherical

"PH"—Pin Hole

"10 I"—10 Diopter Prism Base In (left)

"6 U"—6 Diopter Prism Base Up (right)

"±.50"—±0.50D Fixed Cross Cylinder

"OC"—Occluder

Plus and minus cylinder models available, also the choice of color—black or light grey.

Subject to change in design and/or specifications without advance notice.

**IMPORTANT** In order to obtain the best results with this instrument, please be sure to review all user instructions prior to operation.



TOPCON CORPORATION



TOPCON CORPORATION



TOPCON CORPORATION

75-1 Hasunuma-cho, Itabashi-ku, Tokyo 174-8580, Japan. Phone: 3-3558-2520 Fax: 3-3960-4214 www.topcon.co.jp

#### TOPCON MEDICAL SYSTEMS, INC.

37 West Century Road, Paramus, NJ 07652, U.S.A.  
Phone: 201-261-9450 Fax: 201-387-2710 www.topcon.com

#### TOPCON OMNI SYSTEMS, INC.

Valley Forge Business Center, 2430 Blvd of the Generals,  
Norristown, PA 19403, U.S.A.  
Phone: 610-630-9200 Fax: 610-630-6428 www.topconomni.com

#### TOPCON CANADA INC.

110 Provencher Avenue, Boisbriand QC J7G 1N1, CANADA  
Phone: 450-430-7771 Fax: 450-430-6457 www.topcon.ca

#### TOPCON EUROPE B.V.

Essebaan 11, 2908 LJ Capelle a/d IJssel, THE NETHERLANDS  
Phone: 010-4585077 Fax: 010-4585045 www.topconeuropa.com

#### ITALY OFFICE

Via Montalcione 39, 20092 Cinisello B. mo(MI), ITALY  
Phone: 02-61-25-5693 Fax: 02-61-25-927 www.topcon.it

#### DENMARK OFFICE

Ringsletvej 125, DK-4000 Roskilde, DENMARK  
Phone: 046-327500 Fax: 046-327555

#### IRELAND OFFICE

Unit 69 Western Parkway Business Centre,  
Lower Ballymount Road, Dublin 12, IRELAND  
Phone: 01460-0021 Fax: 01460-0129

#### TOPCON S.A.R.L.

89, Rue de Paris 92585 Clichy, Cedex, FRANCE  
Phone: 01-41069494 Fax: 01-47390251

#### TOPCON DEUTSCHLAND G.m.B.H.

Giesserallee 31, 47877 Willich, Germany  
Phone: 02154-885-100 Fax: 02154-885-111 www.topcon.de

#### TOPCON SCANDINAVIA A.B.

Neongatan 2 S-43151 Molndal, SWEDEN  
Phone: 31-7109200 Fax: 31-288807

#### TOPCON ESPAÑA S.A.

Frederic Mompou 5, ED. Euro 3, 08960 Sant Just Desvern Barcelona, SPAIN  
Phone: 34-93-4734057 Fax: 34-93-4733932 www.topcon.es

#### TOPCON (GREAT BRITAIN) LTD.

Topcon House, Kennet Side, Bone Lane, Newbury,  
Berkshire RG14 5PX United Kingdom  
Phone: 01635-551120 Fax: 01635-551170 www.topcon.com.uk

#### TOPCON SOUTH ASIA PTE.LTD.

Blk 192 Pandan Loop, #07-01 Pantech Industrial Complex, Singapore 128381  
Phone: 62780222 Fax: 62733540 www.topcon.com.sg

#### TOPCON AUSTRALIA PTY.LTD.

408 Victoria Road, Gladesville, NSW 2111, AUSTRALIA  
Phone: 02-9817-4666 Fax: 02-9817-4654 www.topcon.com.au

#### TOPCON INSTRUMENTS (MALAYSIA) SDN. BHD.

Exellia Business Park Block C, Ground & 1st Floor, Jalan Ampang Putra,  
Taman Ampang Hill, 55100 Kuala Lumpur, MALAYSIA  
Phone: 03-42701066 Fax: 03-42704506

#### TOPCON INSTRUMENTS (THAILAND) CO.,LTD.

77/162 Sinn Sathorn Tower, 37th Floor, Krungthornburi Road,  
Klongtonnai, Klongsarn, Bangkok 10600 THAILAND  
Phone: 02-440-1152-7 Fax: 02-440-1158

#### TOPCON KOREA CORPORATION

2F Yooseoung Bldg., 1595-3, Seocho-Dong, Seocho-Gu, Seoul, 137-876, Korea  
Phone: 2-2055-0321-7 Fax: 2-2055-0319 www.topcon.co.kr

#### TOPCON OPTICAL (H.K.) LTD.

2/F., Meecho Industrial Bldg., No.53-35 Au Pui Wan Street,  
Fo Tan Road, Sha Tin, N.T., Hong Kong  
Phone: 852-2690-1328 Fax: 852-2690-2221 www.topcon.com.hk

#### TOPCON CORPORATION BEIJING OFFICE

Room 8A Poly Plaza Building, 14 Dongzhimen  
Nandajie, Dongcheng District, Beijing, 100027 CHINA  
Phone: 10-6501-4191-2 Fax: 10-6501-4190

#### TOPCON CORPORATION SHANGHAI OFFICE

Room 901-903 Lippo Plaza No.222 Huai Hai Zhong Lu Shanghai, 20021 CHINA  
Phone: 21-62701877 Fax: 21-53966485

#### TOPCON CORPORATION BEIRUT OFFICE

P.O. BOX 70-1002 Antelias, BEIRUT-LEBANON  
Phone: 961-4-523525/523526 Fax: 961-4-521119

#### TOPCON CORPORATION DUBAI OFFICE

C/O Atlas Medical FZCO, P.O. BOX 54304, C-25,  
Dubai Airport Free Zone, United Arab Emirates  
Phone: 971-4-2995900 Fax: 971-4-2995901

PRINTED WITH SOY INK

© 2000-2003 TOPCON CORPORATION All Rights Reserved  
Printed in Japan 2003 09-20CMI 733-5 TMS-TS-AS